

**TEKNİK ÖZELLİKLER / Technical Specifications**

Tip / Type	MTM - 600	MTM - 1000	MTM - 1500	MTM - 2000	MTM - 2500
Kat Sayısı / Number of Layer	6 kat/ply	10 kat/ply	15 kat/ply	20 kat/ply	25 kat/ply
Bobin Yükleme Çapı / Feeding Paper Bobin Diameter	Max. 1200 mm				
Bobin Yükleme Geniřlięi / Feeding Paper Bobin Width	Max. 120 mm				
Kaęıt Boru İç Çapı / Paper Tube Inner Diameter	Min. 25 mm / Max. 150 mm				
Kaęıt Boru Et kalınlıęı / Paper Tube Wall Thickness	1,5-2,5mm	1,5-5mm	1,5-7,5mm	1,5-10mm	1,5-14mm
Kaęıt Frenleme Tipi / Paper Braking Type and Quantity	Mekanik / Mechanical				
Tutkal Isıtma Sistemi / Glue Heating System	Yaęlı / With Oil				
Tutkal Pompası Tipi / Pump type	Havalı - with Air				
Hız / Speed	Max. 30 mt/dk - m / min				
Toplam Güç / Total Power	8 kW	11 kW	15 kWh	18,5 kWh	22 kWh

**KAĞIT BESLEME ÜNİTESİ / Paper Feeding Unit****KAĞIT TUTKALLAMA ÜNİTESİ / Paper Gluing Unit****SPIRAL SARIM / Spiral Winding**